



FUEL MANAGEMENT  
SYSTEMS



DISPENSERS



KITS



PUMPS



METERS



NOZZLES

# K150 ATEX

## FEATURES

- HEAVY DUTY CONDITIONS
- HIGH FLOW RATE
- BURSTING PRESSURE 28 BAR
- EASY READING
- 4 FLOW DIRECTIONS

K150 ATEX is expressly engineered to meet the market requirements of a meter suitable for flow rates superior than 120 l/min and that can be used both for fluids such as diesel and biodiesel, as well as in potentially explosives atmosphere; with gasoline for example. K150 is easy to calibrate and ready to use; its aluminium cover and sturdy body make this meter suitable for a wide arrange of application while guaranteeing the same precision and quality that have always featured PIUSI equipment. The mechanical display allows to read quickly the quantity dispensed. It can be installed everywhere thanks to the (optional) 1,5" flange kit. K150 is certified CE, ATEX/UL and tested in PIUSI laboratories for over 4 milion litres to guarantee the maximum reliability.

## PERFORMANCE

UP TO  
**25-150**  
L/MIN  
FLOW RATE

**3,5 BAR**  
MAX  
OPERATING PRESSURE

**± 1%**  
ACCURACY

**0,3%**  
REPEATABILITY





**K150**

OUR PRODUCTS COMPLIES WITH THE FOLLOWING MARKING ATEX

II	2	G	c	IIB	T6
GROUP	CATEGORY	TYPE OF EXPLOSIVE ATMOSPHERE	PROTECTION METHOD	GAS GLASS	TEMPERATURE CLASS

## PACKAGING

CODE	WEIGHT		PACKAGING			BOXES/EUROPALLET	
	KG	LBS	MM	INCH	PCS/BOX		
FO0555A00	2,38	5,25	185X185X170	7,28X7,28X6,69	1	192	240
FO0555B00	2,38	5,25	185X185X170	7,28X7,28X6,69	1	192	240
FO0555C00	2,38	5,25	185X185X170	7,28X7,28X6,69	1	192	240
FO0555D00	2,38	5,25	185X185X170	7,28X7,28X6,69	1	192	240



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

**PIUSI**

INDEX



ANY BIODIESEL



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

## CHART



## DIMENSIONS




Dimensions expressed in millimeters

## IN THE BOX

- K150 ATEX METER
- INSTRUCTION MANUAL

## DETAILS



NUTATING DISK



4 FLOW DIRECTIONS



ATEX APPROVED



METALLIC COVER

## MATERIALS

- BODY AND COVER: ALUMINIUM
- NUTATING DISK CHAMBER: TECHNOPOLYMER

## TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		FLOW DIRECTIONS	PRESSURE		INLET/OUTLET
			L/MIN	GPM		BAR	PSI	BSP
FO0555A00	(EX) K150 METER VER.A ATEX	D G K	25-150	6,6-40		3,5	50	1" BSP
FO0555B00	(EX) K150 METER VER.B ATEX	D G K	25-150	6,6-40		3,5	50	1" BSP
FO0555C00	(EX) K150 METER VER.C ATEX	D G K	25-150	6,6-40		3,5	50	1" BSP
FO0555D00	(EX) K150 METER VER.D ATEX	D G K	25-150	6,6-40		3,5	50	1" BSP

THE PIUSI K150 IS A MECHANICAL METER EXPRESSLY ENGINEERED FOR HEAVY DUTY AND HIGH FLOW RATE APPLICATIONS. IT IS EASY TO CALIBRATE AND READY-TO-USE; ITS ALUMINIUM COVER AND STURDY BODY MAKE THIS METER SUITABLE FOR A WIDE ARRANGE OF APPLICATIONS WHILE GUARANTEEING THE SAME PRECISION AND QUALITY THAT HAVE ALWAYS BEEN A FEATURE OF PIUSI EQUIPMENT.

**K150 ATEX**